# Sample Water Efficient Landscape Worksheet

#### WATER EFFICIENT LANDSCAPE WORKSHEET

This worksheet is filled out by the project applicant and it is a required element of the Landscape Documentation Package.

Reference Eva	apotranspira	ation (ETo)	<u>50.1</u>				
Hydrozone # /Planting Description <sup>a</sup>	Plant Factor (PF)	Irrigation Method <sup>ь</sup>	Irrigation Efficiency (IE)°	ETAF (PF/IE)	Landscape Area (sq, ft,)	ETAF x Area	Estimated Total Water Use (ETWU) <sup>e</sup>
Regular Landscap	be Areas						
1 / FRONT YARD	.8	Spray	.75	0.94	1,000	940	29,198
2 / SIDE YARD	.5	Drip	.81	0.61	300	183	5,685
3 / REAR YARD	.3	Drip	.81	0.37	3,300	1221	37,927
4 / POOL	1.0	n/a	1	1	400	400	12,425
				Totals	<b>5,000</b> (A)	<b>2744</b> (B)	
Special Landscap	e Areas			1			
NONE				1			
				1			
				1			
				Totals	<b>0</b> (C)	<b>0</b> (D)	
				1		ETWU Total	85,234
	Maximum Allowed Water Allowance (MAWA) <sup>e</sup>				85,420		

<sup>c</sup>Irrigation Efficiency

0.81 for drip

0.75 for spray head

**aHydrozone #/Planting Description** E.g

1.) front lawn

2.) low water use plantings

3.) medium water use planting

<sup>e</sup>MAWA (Annual Gallons Allowed) = (Eto) (0.62) [ (ETAF x LA)

+ ((1-ETAF) x SLA)]

where 0.62 is a conversion factor that converts acreinches per acre per year to gallons per square foot per year, LA is the total landscape area in square feet, SLA is the total special landscape area in square feet, and ETAF is .55 for residential areas and 0.45 for nonresidential areas.

<sup>b</sup>Irrigation Method

overhead spray

or drip

### **ETAF Calculations**

#### Regular Landscape Areas

Average ETAF	B ÷ A	0.549
Total Area	(A)	5000
Total ETAF x Area	(B)	2744

Average ETAF for Regular Landscape Areas must be 0.55 or below for residential areas, and 0.45 or below for non-residential areas.

#### All Landscape Areas

Total ETAF x Area	(B+D)	2,744
Total Area	(A+C)	5,000
Sitewide ETAF	(B+D) ÷ (A+C)	0.549

A copy of this form may be obtained from Department of Water Resources website: http://www.water.ca.gov/wateruseefficiency/landscapeordinance/

#### <sup>d</sup>ETWU (Annual Gallons Required) =

Eto x 0.62 x ETAF x Area where 0.62 is a conversion factor that converts acreinches per acre per year to gallons per square foot per year.

# WATER EFFICIENT LANDSCAPE WORKSHEET

This worksheet is filled out by the project applicant and it is a required element of the Landscape Documentation Package.

Reference Evapotranspiration (ETO)							
Hydrozone # /Planting Description <sup>a</sup>	Plant Factor (PF)	Irrigation Method <sup>ь</sup>	Irrigation Efficiency (IE)°	ETAF (PF/IE)	Landscape Area (sq, ft,)	ETAF x Area	Estimated Total Water Use (ETWU) <sup>e</sup>
Regular Landscap	be Areas						
				Totals	(A)	(B)	
Special Landscape Areas							
				1			
				1			
				1			
				Totals	(C)	(D)	
				1		ETWU Total	
	Maximum Allowed Water Allowance (MAWA) <sup>e</sup>						

<sup>c</sup>Irrigation Efficiency

0.81 for drip

0.75 for spray head

<sup>a</sup>Hydrozone #/Planting Description

E.g

1.) front lawn

2.) low water use plantings

3.) medium water use planting

eMAWA (Annual Gallons Allowed) = (Eto) (0.62) [(ETAF x LA)

+ ((1-ETAF) x SLA)]

where 0.62 is a conversion factor that converts acreinches per acre per year to gallons per square foot per year, LA is the total landscape area in square feet, SLA is the total special landscape area in square feet, and ETAF is .55 for residential areas and 0.45 for nonresidential areas.

<sup>b</sup>Irrigation Method

overhead spray

or drip

...

### **ETAF Calculations**

**Regular Landscape Areas** 

Total Area	(A)	
Average ETAF	B÷A	

All Landscape Areas

Total ETAF x Area	(B+D)	
Total Area	(A+C)	
Sitewide ETAF	(B+D) ÷ (A+C)	

A copy of this form may be obtained from Department of Water Resources website: http://www.water.ca.gov/wateruseefficiency/landscapeordinance/

<sup>d</sup>ETWU (Annual Gallons Required) =

Eto x 0.62 x ETAF x Area where 0.62 is a conversion factor that converts acreinches per acre per year to gallons per square foot per year.

Average ETAF for Regular Landscape Areas must be 0.55 or below for residential areas, and 0.45 or below for non-residential areas.